

CHEQUE SCANNER

CheXpress CX35 | The Secure Choice

PARSEO

a Paragon company

The CheXpress CX35 builds on the award-winning CX30 with a sleek dark design and enhanced features such as automated cleaning, a smart button, and optional network connectivity—delivering economical bank-quality performance.

Key features and benefits

Easy single-feed scanning

Optional network-enabled via Ethernet over USB connectivity

Automated cleaning mode

Quiet and fast

Engineered for durability



Single-feed operation with optional pass-through mode

The CX35 retains the popular feed track design from the CX30 that allows items to either scan and return; scan, park and return; or pass straight through the scanner.



Automated cleaning

The LED indicator notifies users when it is time to clean the scanner. The user inserts a cleaning card and presses the button to initiate automated cleaning. The scanner scrubs the cleaning card back and forth as it passes through the track.



Network-enabled on select models

The CX35 can be configured to connect to a network using Ethernet over USB and SecureLink by Digital Check®. This makes the scanner network-enabled via a USB connection to the your workstation using drivers already installed on your computer.



Affordable, Fast, Quality Scanning

The CX35 delivers fast quality scanning and features such as automated cleaning, optional network connectivity, and endorsement at an economical cost. It includes all the features that made its predecessor the most popular RDC scanner in the world and adds multiple improvements Digital Check have recently developed.



Ethernet over USB Connectivity Option

The CheXpress CX35 introduces network functionality to specific models through the use of Ethernet over USB and Digital Check's SecureLink 2.0 API. Furthermore, it includes SimpleSwitch Connectivity enabling users the ability to switch between USB mode or a network connection with a few presses of the Smart Button.



Quality image and MICR capture

The CX35 uses 600 dpi image sensors and Best Read® image enhancement technology to produce legible high-resolution images. The scanner combines MICR reading with OCR verification to increase overall read accuracy. So whether the cheque has a busy background or is written with gel pen ink, the CX35 will provide accurate read rates for your application.

CheXpress CX35

SCANNER SPECIFICATIONS

Scanner dimensions

Height: 18.97 cm (7.47 in)

Width: 9.96 cm (3.92 in)

Length: 23.83 cm (9.38 in)

Weight: 1.69 kg (3.72 lbs.)

Scan modes

Scan and return Scan, park and return

Scan and into exit pocket

Document input and output pockets

Entry Feeder: 1 item

Exit Tray: Up to 5 items

Document handling

Document height: 54 - 108 mm (2.12 in - 4.25 in)

Image capture height: Up to 106 mm (4.17 in)

Document length: 81 - 228 mm (3.19 in - 8.98 in)

Document weight: 60 - 105 gsm bond (16 - 28 lb)

Document thickness: 0.081 - 0.147 mm (0.0032 in - 0.0058 in)

Endorsement option

User-replaceable cartridge (96 dpi printing, 1-line)

User-programmable text

Franker option

User-replaceable franker roller

Image sensor

Resolution: 600 dpi

Light Source: Tri-Color LEDs

MICR/OCR recognition

(Magnetic Ink Character Recognition) for E13B and CMC7
Optical Character Recognition to enhance MICR Read, further enhanced using DCC's Best Read® API function

Image compression standards

JPEG (24-bit color, 8-bit greyscale)

BMP (24-bit color, 4 or 8-bit greyscale)

TIFF Group 4 Black/White

Productivity functions (Smart Button)

Power on/off

Eject

Activate automated cleaning

Connectivity

High-speed USB 2.0 cable and power supply included

Application Programming Interfaces (API)

DCC API

SecureLink 2.0 API (Ethernet over USB model only)

Supported operating systems

DCC API

Windows 11/10 (x86 and x86-64) macOS

SecureLink 2.0 API (Ethernet over USB model)

Windows 11/10 (x86 and x86-64)

macOS (newer versions include an Ethernet over USB driver, older versions require a third-party driver)

Standard warranty

One-year Digital Check Corp. limited product warranty

Electrical

Power Consumption: 24 Watts

Input voltage: 100 to 240 VAC, 50/60 Hz

Separate standard power supply: Auto sensing for voltage

Environmental

Operating temperature: 15° - 32° C (60° - 90° F)

Operating humidity: 35 - 85% non-condensing

Safety certifications:

UL, cUL, CE, BIS

Emissions:

FCC: Class B

ICES-003

CE

Power supply efficiency:

DOE level VI RoHS compliant

Part Numbers

Standard model:

157000-01 - CX35 non-inkjet

Optional models:

157000-02 - CX35 with inkjet endorser

157001-01 - CX35 non-inkjet with franker

157001-02 - CX35 with inkjet endorser and franker

157010-01 - CX35 network non-inkjet

157010-02 - CX35 network inkjet endorser

Parseq, Lowton Way, Hellaby, Rotherham, South Yorkshire S66 8RY

+44(0) 1709 448000 | info@parseq.com

The Digital Check Logo, CheXpress, Best Read, Securelink by Digital Check and The Secure Choice are registered US trademarks of Digital Check Corp. All other product names mentioned herein may be trademarks of their respective owners.

Please note: All scanners are supplied and invoiced by Parseq, Lowton Way, Hellaby, Rotherham, South Yorkshire S66 8RY (Reg. No. 05815806)